

BUILDING TRUST

	loor [®] -3570	
	028701	ARAMETROCH
1	JEDINEČNÝ IDENTIFIKAČNÝ KÓD TYPU VÝROBKU:	40028701
2	ZAMÝŠĽANÉ POUŽITIE/POUŽITIA:	Syntetický poterový materiál na použitie v interiéri
3	VÝROBCA:	Sika Services AG Tüffenwies 16-22 8064 Zürich Švajčiarsko
4	SPLNOMOCNENÝ ZÁSTUPCA:	Sika Slovensko, spol. s r.o. Rybničná 38/e 831 06 Bratislava, Slovenská republika
5	SYSTÉM(-Y) POSUDZOVANIA A OVEROVANIA NEMENNOSTI PARAMETROV:	EN 13813: Systém 4 (na použitie v interiéri)
6a	HARMONIZOVANÁ NORMA:	EN 13813:2002
	Notifikovaný(-é) subjekt(-y):	0921 0767

Vyhlásenie o parametroch Sikafloor®-3570 40028701 4.12.2018 , ver. 2 1008 7 DEKLAROVANÉ PARAMETRE

Testovaný ako súčasť systému – skladba: primer Sikafloor®-161, Sikafloor®-264 (+ 70% krem. piesku 0,1 – 0,3 mm) a Sikafloor®-3570

Podstatné vlastnosti	Parametre	Ανςρ	Harmonizovana technická špecifikácia
Reakcia na oheň	B _{fl}	Systém 4	
Uvoľňovanie korozívnych látok	SR	Systém 4	
Presiakavosť	NPD	Systém 4	
Odolnosť proti opotrebovaniu	≤ AR1 ^{1]}	Systém 4	
Prídržnosť	≥ B2,0	Systém 4	
Odolnosť proti rázu	≥ IR10	Systém 4	EN 13813:2002
Zvuková izolácia	NPD	Systém 4	
Pohltivosť zvuku	NPD	Systém 4	
Tepelný odpor	NPD	Systém 4	
Odolnosť proti chemikáliám	NPD	Systém 4	

1) min. klasifikácia, prosím vyžiadajte si skúšobný protokol k produktu

8 VHODNÁ TECHNICKÁ DOKUMENTÁCIA A/ALEBO ŠPECIFICKÁ TECHNICKÁ DOKUMENTÁCIA

Uvedené parametre výrobku sú v zhode so súborom deklarovaných parametrov. Toto vyhlásenie o parametroch sa v súlade s nariadením (EÚ) č. 305/2011 vydáva na výhradnú zodpovednosť uvedeného výrobcu.

Podpísal(-a) za a v mene Sika Slovensko, spol. s r.o.:

Meno : Ing. Henrie Funkcia: Manažér V Bratislave, dňa 5	kvality a EMS	Meno : Ing. Mare Funkcia: Konateľ V Bratislave, dňa	Sika Slovensko, spol. s r.o.
Abson	ira		h
	Koniec informácií požadovar	ých Nariadením (EU) č. 305/201	1
SUVISIACE VYHLÄSEN			¥
Názov produktu		technická špecifikácia	Číslo VoP
Sikafloor®-3570	EN 1504-2:2004		16216638

Vyhlásenie o parametroch Sikafloor®-3570 40028701 4.12.2018 , ver. 2 1008



	CE
	14
	EN 13813:2002
	VoP č. 40028701
Sika Ser	vices AG, Zürich, Švajčiarsko
Notifi	kovaný subjekt 0921, 0767
Syntetický poter	rový materiál na použitie v interiéri
Reakcia na oheň	B _{fl}
Uvoľňovanie korozívnych látok	SR
Odolnosť proti opotrebovaniu	≤ AR1
	≥ B2,0
Prídržnosť	≥ IR10

INFORMÁCIE O OCHRANE ŽIVOTNÉHO PROSTREDIA, ZDRAVIA A BEZPEČNOSTI PRI PRÁCI (REACH)

Informácie a pokyny týkajúce sa bezpečnej prepravy, manipulácie, skladovania a likvidácie chemických produktov nájdete v aktuálnom vydaní karty bezpečnostných údajov, ktorá obsahuje fyzikálne, ekologické, toxikologické a iné údaje, týkajúce sa bezpečnej manipulácie s produktom.

PRÁVNE OZNÁMENIE

Informácie a najmä odporúčania, vzťahujúce sa na aplikáciu a použitie produktov spoločnosti Sika koncovými užívateľmi, sa poskytujú v dobrej viere na základe súčasných vedomostí a skúseností spoločnosti Sika s týmito produktmi, za predpokladu správneho skladovania, manipulácie a aplikácie za bežných podmienok v súlade s doporučeniami spoločnosti Sika. V praxi sa vzhľadom na rozdiely v materiáloch, podkladoch a v skutočných podmienkach na danom mieste nemôže vyvodzovať z týchto informácií ani z písomných odporúčaní, či iného poskytnutého poradenstva žiadna záruka za predaj alebo vhodnosť a použiteľnosť pre určitý účel, ani žiadna zodpovednosť vyplývajúca z akéhokoľvek právneho vzťahu. Spracovávateľ produktu musí vopred vyskúšať vhodnosť produktu pre plánované použitie a účel. Spoločnosť Sika si vyhradzuje právo na zmenu vlastností svojich produktov. Vlastnícke práva tretích strán musia byť dodržané. Všetky objednávky sa akceptujú v súlade s platnými všeobecnými obchodnými podmienkami. Užívatelia sú vždy povinní preštudovať si poslednú verziu príslušného produktového listu, ktorého kópiu zašleme na vyžiadanie alebo je k dispozícii na www.sika.sk

Vyhlásenie o parametroch Sikafloor®-3570 40028701 4.12.2018 , ver. 2 1008



Pre ďalšie informácie o výrobku kontaktujte: Sika Slovensko, spol. s r.o., Rybničná 38/e, 831 06 Bratislava tel: +421 2 49200403 Fax: +421 2 49200444 e-mail: sika@sk.sika.com

Vyhlásenie o parametroch Sikafloor®-3570 40028701 4.12.2018 , ver. 2 1008



BUILDING TRUST

Sikafloor[®]-3570 DECLARATION OF PERFORMANCE No. 40028701

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	40028701
2	INTENDED USE/S	Synthetic resin screed for internal uses
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	EN 13813: System 4 (for internal uses)
6a	HARMONISED STANDARD:	EN 13813:2002
	Notified body/ies:	0921 0767

Declaration of Performance Sikafloor®-3570 40028701 04.12.2018 , ver. 2 1008 7 DECLARED PERFORMANCE/S

Tested as a part of a system build-up with Primer Sikafloor[®]-161, Sikafloor[®]-264 (+ 70% quartz sand 0,1-0,3mm) and Sikafloor[®]-3570

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire:	Bfl	System 4	
Release of corrosive substances:	SR	System 4	
Water permeability:	NPD	System 4	
Wear resistance:	$\leq AR1^{1)}$	System 4	
Bond strength:	≥ B2,0	System 4	
Impact resistance:	≥ IR10	System 4	EN 13813:2002
Sound insulation:	NPD	System 4	
Sound absorption:	NPD	System 4	
Thermal resistance:	NPD	System 4	
Chemical resistance:	NPD	System 4	

 $^{\mbox{\tiny 1)}}$ Min. classification, please refer to the individual test certificate.

Declaration of Performance Sikafloor®-3570 40028701 04.12.2018 , ver. 2 1008



8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Jochen Grötzinger Function: Research and Development Stuttgart, 04.12.2018

ritz

Name : Dr. Stefan Kühner Function: Marketing

Stuttgart, 04.12.2018

jo S. Tukne

Stuttgart, 04.12.2018

Name : Dr. Heinz Ephardt

Function: Quality control

quill

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product name	Harmonised standard	DoP number
Sikafloor [®] -3570	EN 1504-2:2004	16216638

Declaration of Performance Sikafloor®-3570 40028701 04.12.2018 , ver. 2 1008



	14	
	EN 13813: 2002	
D	oP No. 40028701	
Sika Servio	es AG, Zürich, Switzerland	
Notif	fied Body 0921, 0767	
Synthetic re	sin screed for internal uses	
Reaction to fire:	B _{fl}	
Reaction to fire: Release of corrosive substances:	B _{fl} SR	
	· · · · · · · _ /	
Release of corrosive substances:	SR	

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

FOR FURTHER INFORMATION:

Sika Services AG Tüffenwies 16 8048 Zürich Telefon +41-58 436 40 40 Telefax +41-58 436 53 54 www.sika.ch

Declaration of Performance Sikafloor®-3570 40028701 04.12.2018 , ver. 2 1008







