

# Sikafloor-3000

## VYHLÁSENIE O PARAMETROCH č. 33841553

1	<b>JEDINEČNÝ IDENTIFIKAČNÝ KÓD TYPU VÝROBKU:</b>	33841553
2	<b>ZAMÝŠĽANÉ POUŽITIE/POUŽITIA:</b>	Syntetický poterový materiál na použitie v interiéri
3	<b>VÝROBCA:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	<b>SPLNOMOCNENÝ ZÁSTUPCA:</b>	
5	<b>SYSTÉM(-Y) POSUDZOVANIA A OVEROVANIA NEMENNOSTI PARAMETROV:</b>	EN 13813: Systém 4 (na použitie v interiéri)
6a	<b>HARMONIZOVANÁ NORMA:</b>	EN 13813:2002
	Notifikovaný(-é) subjekt(-y):	0921 1611

### Vyhlásenie o parametroch

Sikafloor-3000  
33841553  
31.07.2017 , ver. 2  
1008

**7 DEKLAROVANÉ PARAMETRE** Testovaný systém: skladba Sika ComfortFloor so Sikafloor-161, Sikafloor-3000 a Sikafloor-304 W

Podstatné vlastnosti	Parametre	AVCP	Harmonizovaná technická špecifikácia
Reakcia na oheň	B <sub>fl</sub>	System 4	EN 13813:2002
Uvoľňovanie korozívnych látok	SR	System 4	
Presiakavosť	NPD	System 4	
Odolnosť proti opotrebovaniu	AR0,5 <sup>1)</sup>	System 4	
Prídržnosť	≥ B2,0	System 4	
Odolnosť proti rázu	IR4	System 4	
Zvuková izolácia	NPD	System 4	
Pohltivosť zvuku	NPD	System 4	
Tepelný odpor	NPD	System 4	
Odolnosť proti chemikáliám	NPD	System 4	

1) min. klasifikácia, prosím vyžiadajte si skúšobný protokol k produktu

**8 VHODNÁ TECHNICKÁ DOKUMENTÁCIA A/ALEBO ŠPECIFICKÁ TECHNICKÁ DOKUMENTÁCIA**

Uvedené parametre výrobku sú v zhode so súborom deklarovateľných parametrov. Toto vyhlásenie o parametroch sa v súlade s nariadením (EÚ) č. 305/2011 vydáva na výhradnú zodpovednosť uvedeného výrobcu.

Podpísal(-a) za a v mene výrobcu:

Name : Jochen Grötzingler  
Function: Research and Development  
Stuttgart, 31.07.2017

Name : Dr. Stefan Kühner  
Function: Marketing  
Stuttgart, 31.07.2017

Name : Dr. Heinz Ehardt  
Function: Quality control  
Stuttgart, 31.07.2017

Koniec informácií požadovaných Nariadením (EÚ) č. 305/2011

**SÚVISIACE VYHLÁSENIE O PARAMETROCH**

Názov produktu  
Sikafloor-3000

Harmonizovaná technická špecifikácia  
EN 1504-2:2004

Číslo VoP  
97212222

**Vyhlásenie o parametroch**

Sikafloor-3000  
33841553  
31.07.2017, ver. 2  
1008



15

DIN EN 13813:2002

VoP č. 33841553

Sika Services AG, Zurich, Switzerland

Notifikovaný subjekt 0921, 1611

Syntetický poterový materiál na použitie v interiéri

Reakcia na oheň	B <sub>n</sub>
Uvoľňovanie korozívnych látok	SR
Odolnosť proti opotrebovaniu	AR0,5 <sup>1)</sup>
Prídržnosť	≥ B2,0
Odolnosť proti rázu	IR4

<http://dop.sika.com>

## INFORMÁCIE O OCHRANE ŽIVOTNÉHO PROSTREDIA, ZDRAVIA A BEZPEČNOSTI PRI PRÁCI (REACH)

Informácie a pokyny týkajúce sa bezpečnej prepravy, manipulácie, skladovania a likvidácie chemických produktov nájdete v aktuálnom vydaní karty bezpečnostných údajov, ktorá obsahuje fyzikálne, ekologické, toxikologické a iné údaje, týkajúce sa bezpečnej manipulácie s produktom.

## PRÁVNE OZNÁMENIE

Informácie a najmä odporúčania, vzťahujúce sa na aplikáciu a použitie produktov spoločnosti Sika koncovými užívateľmi, sa poskytujú v dobrej viere na základe súčasných vedomostí a skúseností spoločnosti Sika s týmito produktmi, za predpokladu správneho skladovania, manipulácie a aplikácie za bežných podmienok v súlade s doporučeniami spoločnosti Sika. V praxi sa vzhľadom na rozdiely v materiáloch, podkladoch a v skutočných podmienkach na danom mieste nemôže vyvodzovať z týchto informácií ani z písomných odporúčaní, či iného poskytnutého poradenstva žiadna záruka za predaj alebo vhodnosť a použiteľnosť pre určitý účel, ani žiadna zodpovednosť vyplývajúca z akéhokoľvek právneho vzťahu. Spracovávateľ produktu musí vopred vyskúšať vhodnosť produktu pre plánované použitie a účel. Spoločnosť Sika si vyhradzuje právo na zmenu vlastností svojich produktov. Vlastnícke práva tretích strán musia byť dodržané. Všetky objednávky sa akceptujú v súlade s platnými všeobecnými obchodnými podmienkami. Užívateľia sú vždy povinní preštudovať si poslednú verziu príslušného produktového listu, ktorého kópiu zašleme na vyžiadanie alebo je k dispozícii na [www.sika.sk](http://www.sika.sk)

### Pre ďalšie informácie o výrobku kontaktujte:

Sika Slovensko, spol. s r.o., Rybníčná 38/e, 831 06 Bratislava  
tel: +421 2 49200403  
Fax: +421 2 49200444  
e-mail: [sika@sk.sika.com](mailto:sika@sk.sika.com)

### Vyhlásenie o parametroch

Sikafloor-3000  
33841553  
31.07.2017, ver. 2  
1008



**Vyhlasenie o parametroch**  
Sikafloor-3000  
33841553  
31.07.2017 , ver. 2  
1008

**4/4**

**BUILDING TRUST**



---

# Sikafloor-3000

---

## DECLARATION OF PERFORMANCE

### No. 33841553

---

<b>1</b>	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	33841553
<b>2</b>	<b>INTENDED USE/S</b>	Synthetic resin screed for internal uses
<b>3</b>	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich
<b>4</b>	<b>AUTHORISED REPRESENTATIVE:</b>	
<b>5</b>	<b>SYSTEM/S OF AVCP:</b>	EN 13813: System 4 (for internal uses)
<b>6a</b>	<b>HARMONISED STANDARD:</b>	EN 13813: 2002
	Notified body/ies:	0921 1611

#### Declaration of Performance

33841553 - Sikafloor-3000  
31.07.2017 , ver. 2  
1008

**7 DECLARED PERFORMANCE/S** Tested system: build up as Sika-ComfortFloor with Sikafloor-161, Sikafloor-3000 and Sikafloor-304 W

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire:	B <sub>fl</sub>	System 4	EN 13813: 2002
Release of corrosive substances:	SR	System 4	
Water permeability:	NPD	System 4	
Wear resistance:	AR0,5 <sup>1)</sup>	System 4	
Bond strength:	≥ B2,0	System 4	
Impact resistance:	IR4	System 4	
Sound insulation:	NPD	System 4	
Sound absorption:	NPD	System 4	
Thermal resistance:	NPD	System 4	
Chemical resistance:	NPD	System 4	

<sup>1)</sup> Min. classification, please refer to the individual test certificate.

**Declaration of Performance**

33841553 - Sikafloor-3000  
31.07.2017 , ver. 2  
1008



---

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -  
SPECIFIC TECHNICAL DOCUMENTATION**

---

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.



Signed for and on behalf of the manufacturer by:

---

Name : Jochen Grötzinger  
Function: Research and  
Development  
Stuttgart, 31.07.2017

Name : Dr. Stefan Kühner  
Function: Marketing  
Stuttgart, 31.07.2017

Name : Dr. Heinz Ephardt  
Function: Quality control  
Stuttgart, 31.07.2017



---

End of information as required by Regulation (EU) No 305/2011

## RELATED DECLARATION OF PERFORMANCE

---

Product name	Harmonised standard	DoP number
Sikafloor-3000	EN 1504-2: 2004	97212222

---

### Declaration of Performance

33841553 - Sikafloor-3000  
31.07.2017 , ver. 2  
1008



15

DIN EN 13813: 2002

DoP No. 33841553

Sika Services AG, Zürich, Switzerland

Notified Body 0921, 1611

Synthetic resin screed for internal uses

Reaction to fire:	B <sub>f1</sub>
Release of corrosive substances:	SR
Wear resistance:	AR0,5
Bond strength:	≥ B2,0
Impact resistance:	IR4

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

## FOR FURTHER INFORMATION:

Sika Services AG  
Tüffenwies 16  
8048 Zürich

Telefon +41-58 436 40 40  
Telefax +41-58 436 53 54  
[www.sika.ch](http://www.sika.ch)

## Declaration of Performance

33841553 - Sikafloor-3000  
31.07.2017 , ver. 2  
1008

4/5

**BUILDING TRUST**







**Declaration of Performance**

33841553 - Sikafloor-3000  
31.07.2017 , ver. 2  
1008

