

Sikafloor®-3000 FX

VYHLÁSENIE O PARAMETROCH č. 44999561

1	JEDINEČNÝ IDENTIFIKAČNÝ KÓD TYPU VÝROBKU:	44999561
2	ZAMÝŠĽANÉ POUŽITIE/POUŽITIA:	EN 13813:2002 Syntetický poterový materiál na použitie v interiéri
3	VÝROBCA:	Sika Services AG Tüffenwies 16-22 8064 Zürich Švajčiarsko
4	SPLNOMOCNENÝ ZÁSTUPCA:	Sika Slovensko, spol. s r.o. Rybničná 38/e 831 06 Bratislava Slovenská republika
5	SYSTÉM(-Y) POSUDZOVANIA A OVEROVANIA NEMENNOSTI PARAMETROV:	System 4 (na použitie v interiéri)
6a	HARMONIZOVANÁ NORMA:	EN 13813:2002
	Notifikovaný(-é) subjekt(-y):	Nie je potrebný notifikovaný subjekt

Vyhlásenie o parametroch

Sikafloor®-3000 FX
44999561
2018.10, ver. 1
1041

7 DEKLAROVANÉ PARAMETRE

Podstatné vlastnosti	Parametre	AVCP	Harmonizovaná technická špecifikácia
Reakcia na oheň	B _{fl}	Systém 4	EN 13813:2002
Uvoľňovanie korozívnych látok	SR	Systém 4	
Presiakavosť	NPD	Systém 4	
Odolnosť proti opotrebovaniu	AR2	Systém 4	
Prídržnosť	> B2	Systém 4	
Odolnosť proti rázu	IR4	Systém 4	
Zvuková izolácia	NPD	Systém 4	
Pohltivosť zvuku	NPD	Systém 4	
Tepelný odpor	NPD	Systém 4	
Odolnosť proti chemikáliám	NPD	Systém 4	



8 VHODNÁ TECHNICKÁ DOKUMENTÁCIA A/ALEBO ŠPECIFICKÁ TECHNICKÁ DOKUMENTÁCIA

Uvedené parametre výrobku sú v zhode so súborom deklarovateľných parametrov. Toto vyhlásenie o parametroch sa v súlade s nariadením (EÚ) č. 305/2011 vydáva na výhradnú zodpovednosť uvedeného výrobcu.

Podpísal(-a) za a v mene výrobcu:

Meno : Ing. Henrieta Absolonová
Funkcia: Manažér kvality a EMS
V Bratislave, dňa 25.10.2019

Meno : Ing. Marek Mikuš
Funkcia: Konateľ Sika Slovensko, spol. s r.o.
V Bratislave, dňa 25.10.2019



Koniec informácií požadovaných Nariadením (EÚ) č. 305/2011

Vyhlásenie o parametroch

Sikafloor®-3000 FX
44999561
2018.10, ver. 1
10418



15

EN 13813:2002

VoP č. 44999561

Sika Services AG, Zürich, Švajčiarsko

Nie je potrebný notifikovaný subjekt

Syntetický poterový materiál na použitie v interiéri

Reakcia na oheň	B _{fl}
Uvoľňovanie korozívnych látok	SR
Odolnosť proti opotrebovaniu	AR2
Prídržnosť	> B2
Odolnosť proti rázu	IR4

<http://dop.sika.com>

INFORMÁCIE O OCHRANE ŽIVOTNÉHO PROSTREDIA, ZDRAVIA A BEZPEČNOSTI PRI PRÁCI (REACH)

Informácie a pokyny týkajúce sa bezpečnej prepravy, manipulácie, skladovania a likvidácie chemických produktov nájdete v aktuálnom vydaní karty bezpečnostných údajov, ktorá obsahuje fyzikálne, ekologické, toxikologické a iné údaje, týkajúce sa bezpečnej manipulácie s produktom.

PRÁVNE OZNÁMENIE

Informácie a najmä odporúčania, vzťahujúce sa na aplikáciu a použitie produktov spoločnosti Sika koncovými užívateľmi, sa poskytujú v dobrej viere na základe súčasných vedomostí a skúseností spoločnosti Sika s týmito produktmi, za predpokladu správneho skladovania, manipulácie a aplikácie za bežných podmienok v súlade s doporučeniami spoločnosti Sika. V praxi sa vzhľadom na rozdiely v materiáloch, podkladoch a v skutočných podmienkach na danom mieste nemôže vyvodzovať z týchto informácií ani z písomných odporúčaní, či iného poskytnutého poradenstva žiadna záruka za predaj alebo vhodnosť a použiteľnosť pre určitý účel, ani žiadna zodpovednosť vyplývajúca z akéhokoľvek právneho vzťahu. Spracovávateľ produktu musí vopred vyskúšať vhodnosť produktu pre plánované použitie a účel. Spoločnosť Sika si vyhradzuje právo na zmenu vlastností svojich produktov. Vlastnícke práva tretích strán musia byť dodržané. Všetky objednávky sa akceptujú v súlade s platnými všeobecnými obchodnými podmienkami. Užívateľia sú vždy povinní preštudovať si poslednú verziu príslušného produktového listu, ktorého kópiu zašleme na vyžiadanie alebo je k dispozícii na www.sika.sk

Vyhlasenie o parametroch

Sikafloor®-3000 FX
44999561
2018.10, ver. 1
10418

3/4

BUILDING TRUST



Sikafloor®-3000 FX

DECLARATION OF PERFORMANCE

No. 44999561

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	44999561
2	INTENDED USE/S	EN 13813:2002 Synthetic resin screed for internal uses
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4 (for internal uses)
6a	HARMONISED STANDARD:	EN 13813:2002
	Notified body/ies:	No Notified Body required

Declaration of Performance

Sikafloor®-3000 FX

44999561

2018.10 , ver. 1

1041

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire:	Bfl	System 4	EN 13813:2002
Release of corrosive substances:	SR	System 4	
Water permeability:	NPD	System 4	
Wear resistance:	AR2	System 4	
Bond strength:	>B2	System 4	
Impact resistance:	IR4	System 4	
Sound insulation:	NPD	System 4	
Sound absorption:	NPD	System 4	
Thermal resistance:	NPD	System 4	
Chemical resistance:	NPD	System 4	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
Function: Corporate Standardization
and Approvals
At Warsaw on 02 October 2018

Name : Tatiana Ageyeva
Function: Standardization and Approvals
At Warsaw on 02 October 2018



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sikafloor®-3000 FX
44999561
2018.10 , ver. 1
1041



15

EN 13813:2002

DoP No. 44999561

Sika Services AG, Zürich, Switzerland

No Notified Body required

Synthetic resin screed for internal uses

Reaction to fire:	B _{f1}
Release of corrosive substances:	SR
Wear resistance:	AR2
Bond strength:	>B2
Impact resistance:	IR4

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.


FOR FURTHER INFORMATION:

Sika Services AG
Tüffenwies 16
8048 Zürich

Telefon +41-58 436 40 40
Telefax +41-58 436 53 54
www.sika.ch

Declaration of Performance

Sikafloor®-3000 FX
44999561
2018.10 , ver. 1
1041



Declaration of Performance

Sikafloor®-3000 FX

44999561

2018.10 , ver. 1

1041

4/4

BUILDING TRUST

